

## Back-up alarms (extract) GREWUS

| Product              | Operating voltage (V) | dB     | Frequency (kHz) | Tone constant-pulse-sirene |       |        | Weight in gr. | Current consumption | Operating temperature | IP | Contact  |
|----------------------|-----------------------|--------|-----------------|----------------------------|-------|--------|---------------|---------------------|-----------------------|----|----------|
|                      |                       |        |                 | Constant                   | Pulse | Sirene |               |                     |                       |    |          |
| BUS 102C9-30VBW-01 A | 9-30                  | 102    | 1400 ±200       | Constant                   |       |        |               | < 250 mA            | -40°C - +85°C         | 67 | Wire     |
| HU 105S12VW A        | 8-15                  | 105    | 3000 ±500       |                            |       | Sirene |               | < 300 mA            | -20°C - +80°C         | 67 | Wire     |
| HU 110C24VB A        | 15-30                 | 110    | 3000 ±200       | Constant                   |       |        |               | < 300 mA            | -20°C - +80°C         | 67 | Wire     |
| HU 110P12VB A        | 8-15                  | 110    | 3000 ±200       |                            | Pulse |        | 85            | < 300 mA            | -20°C - +80°C         | 67 | Wire     |
| HU 110P24VB D        | 15-30                 | 110    | 3000 ±200       |                            | Pulse |        | 136           | < 300 mA            | -30°C - +85°C         | 67 | Wire     |
| HU 2SPL A            | 8-30                  | 95/78  | 1000 ±300       |                            | Pulse |        | 85            | < 300 mA            | -20°C - +80°C         | 67 | Wire     |
| HU 2SPL-Speaker A    | 11-28                 | 96/80  | 1000 ±300       |                            | Pulse |        | 170           | < 300 mA            | -20°C - +80°C         | 67 | Wire     |
| HU 97C3-30VB A       | 3,5-30                | 97     | 3000 ±200       | Constant                   |       |        | 150           | < 300 mA            | -20°C - +80°C         | 67 | Wire     |
| HU 97P3-30VB A       | 3,5-30                | 97     | 3000 ±200       |                            | Pulse |        | 150           | < 300 mA            | -20°C - +80°C         | 67 | Wire     |
| HU Smart NVA         | 9-28                  | 85     | 1000 ±200       |                            | Pulse |        | 250           | <400 mA             | -20°C - +70°C         | 67 | Terminal |
| HUS 96P12VBA         | 11-15                 | 96     | 1000 ±300       |                            | Pulse |        |               | < 300 mA            | -20°C - +80°C         | 67 | Wire     |
| HU 97P12VBA          | 8-15                  | 99     | 3000 ±200       |                            | Pulse |        |               | < 300 mA            | -40°C - +85°C         | 67 | Wire     |
| HUS 73P12VB A        | 9-18                  | 73 ± 3 | 1000 ± 300      |                            | Pulse |        | 50            | < 50 mA             | -20°C - +70°C         | 67 | Wire     |

